Behind every conceivable industry and application environment; heavy or light duty, indoor or outdoor, clean or contaminated, high or low temperature, Renold chain is hard at work delivering performance and increasing productivity.

Whatever your working environment or chain requirement- Renold has the chain for you.

Best	*
Better	•••
Good	••
Standard	•
Not Recommended	

	43		Sone	reign Syn		Hidro se	Staliness Vice	
	Sine Whi	ney	ORC OVE	reign	State	Sino de	Aice /	O'E CO
Corrosion Resistance					•	•	•••	*
Fatigue & Wear Resistance	•••	••	•	•••	*	•••	••	•
Wet or Underwater Application							•••	*
No Lubrication Required						*		
High Shock Loads (HV Series*)	*	••		••	•••		••	•
Abrasion Resistant	••			*	•			
Dirty & Dusty Environment	••			*	•		•••	•••
FDA Approved for Food Contact								•••
USDA H1 Lubricant						•••		*
Temperature Ranges	-24°to 350°F	-24°to 350°F	-24°to 350°F	-24°to 350°F	-24°to 350°F	-24°to 302°F	-24°to 350°F	(304)1200° (316)1300°
Attachments Available	Yes	Yes	Yes	No	No	Yes	Yes	Yes

^{*} HV Series applies to Blue Box only.

^{***} Every application is unique. This chart is meant as a guideline. Temperature ranges can vary based upon application and lubrication. We recommend a consultation with a member of the Renold Engineering Team, call 1-800-251-9012.